

SEALER STRIPPER

Premium Concrete Coatings Remover

DESCRIPTION

SEALER STRIPPER is a concrete coating remover designed to remove most types of coatings from concrete surfaces without harming the concrete itself. SEALER STRIPPER works on acrylic, varnish, latex, lacquer, urethane, and most epoxies.

FEATURES

★ Long open time for workability ★ Does not damage concrete ★ Easy to use

APPLICATION

Test a small area for results before application. Roll Stripper on concrete. Allow to sit for a minimum of 30 minutes. If surface is exterior, power wash residue away with water. For interior, use a scrub brush and a flat blade. Stubborn coatings will require multiple applications of stripper. Clean with CLEMONS DEGREASER NEUTRALIZER and rinse with clean water. NOTE: Timing is critical. Test film periodically to determine readiness for removal. Removing too soon will leave coating. If left too long, coating will dry and re-seal. Reapplication of the stripper will "reactivate" the surface if it has dried.

NET COVERAGE RATE

Use as approximately as many gallons of STRIPPER as gallon of sealer that were applied. If coatings are unknown, use approximately 100 -200 ft² per gallon.

TECHNICAL DATA

Flash Point: 147.2° F

HMIS

Health	2	Flammability	4
Reactivity	0	Protection	I

PRECAUTION

Use safety glasses, rubber gloves, and a respirator with organic vapor cartridges. Clothe all areas of your body. Avoid breathing vapors. Pre-soak with water and cover any plants that may come in contact with stripper or its residue. Store in cool shaded area. Store material in a cool, dry area out of direct sunlight.

CLEANUP

Clean tools with soapy water.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052