

RESTORATION CLEANER AND STAIN REMOVER

DESCRIPTION AND USE

- * OneRestore is appropriate for multiple surface restoration
- * Restores virtually every type of exterior building cladding including limestone, terra cotta, concrete, EIFS, glass, anodized aluminum, stainless steel, brick, block, wood, cast stone, unpolished marble, granite, exterior tile, aluminum, painted surfaces and vinyl
- * Removes virtually every color stain from most surfaces
- * Removes, cleans and de-blushes many sealers

ADVANTAGES

- * Excellent for removing virtually all stains including mineral and metal oxide stains.
- * Reduces liability.
- * Low odor means it can easily be used for interior cleaning
- * Spray-on/spray-off application process improves productivity
- * One product restoration simplifies the process and reduces protection requirements
- * VOC compliant

LIMITATIONS

- * Rinse quickly when on glass and anodized aluminum.
- * Do not use on polished marble and metallic oxide film used for tinting glass.
- * Do not allow product to dry on surface. Rinse thoroughly.
- * Not recommended for restoration of antique glass, brass, copper or bronze.

TECHNICAL DATA

Appearance & Odor: Amber liquid, mild odor.
Physical State: Liquid
Vapor Pressure (mmHg): N/A
Vapor Density (air=1): N/A
Boiling Point: 212° F
Freezing/Melting Point: N/A
Specific Gravity (water =1): 1.117
Evaporation Rate: Slower than ether
Solubility in Water: Complete

PREPARATION

Protect adjacent and surrounding surfaces from exposure to the cleaning solution. Cover landscape with polyethylene or other proven protective material. Wetting down foliage with water before and after the cleaning process can be an option.

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° Fahrenheit or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

Use undiluted (straight) for most applications.
Note: Diluting can be done, follow the pre-testing process to determine the proper dilution for the situation.

APPLICATION INSTRUCTIONS

Before applying, read "Preparation" section and "Precautionary Measures" under Safety Information. Recommended application is by low-pressure sprayer; brushing is not necessary. One single undiluted application will remove many stains. For deep stain removal from porous surfaces, pre-wet (do not soak) the surface with water. Use a double undiluted application, spaced three to five minutes apart without rinsing in between the applications. Follow with a pressure wash rinse of approximately 1,000 psi - 3,000 psi for the best results. Use lower rinse pressures when cleaning sensitive substrates. Extended dwell time is very important when using this product. Do not allow product to dry on the surface. Always rinse thoroughly.

COVERAGE RATES

Coverage rates vary from 75 – 250 sq. ft. per gallon depending on the surface porosity, texture, and severity of staining.



RESTORATION CLEANER AND STAIN REMOVER

SUITABLE SUBSTRATES

Brick, limestone, sandstone, concrete, precast, exposed aggregate, granite, unpolished marble, synthetic stone, terrazzo, anodized aluminum, EIFS, uncoated stainless steel, stucco, roofs, glass and virtually any type of construction material. Always test product in a small area before beginning project.

STAIN REMOVAL

Vanadium, manganese, metal or mineral oxide stains, pollution stains, concrete leaching, caulk bleed, water hardness stains and sealer overspray from glass, and sealants.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Do not get in eyes, on skin, or clothing. If material comes in contact with clothing, wash before reuse. The product contains Hydrochloric Acid. Avoid breathing fumes. Use adequate ventilation. Though the potential for fuming is minimal, take precautions to avoid exposing building occupants to fumes above PEL (permissible exposure limits) for product. Keep container closed after handling. Applicators should wear rain suit (plastic, rubber, or PVC), boots, gloves, face shields, and/or goggles to avoid splash to bare skin and eyes. Avoid drifting of material and rinse water onto autos and pedestrians by protecting or diverting such traffic. Do not dilute OneRestore with any product except water. Do not use for any other applications other than specified. Dispose of any empty containers according to federal, state, and local requirements. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear proper protective equipment while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place away from alkali / base. Do not allow this product to freeze. Vent bung cap before opening. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue and vapors and must be handled as if full. Completely rinse drum prior to disposal.

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flood with water for fifteen minutes and seek medical attention. Remove contact lenses immediately.
Skin: Wash off with soap and water. Use good skin emollient. If irritation develops, seek medical attention.
Ingestion: Drink lots of water to dilute. Seek immediate medical attention. Do not induce vomiting.
Inhalation: Remove to fresh air. Call physician and seek medical attention if irritation develops.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

